

ILS or LOC RWY 22

LOC I-CVS

109.7

APCH CRS

218°

Rwy Idg

10,003

TDZE

4295

Arprt Elev

4295

AL-512 [USAF]

CANNON AFB (KCVS)

▽

* When ALS inop, increase RVR to 40 and vis to ¾ miles.

** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile, CAT CDE vis to 1 ¼ miles.

ALS F-1

A1

† MISSED APPROACH: Climb to 6000 out CVS TACAN R-220 to 6 DME (JEBES) then turn left climbing to 7000 intercept CVS R-193 to 12 DME (CLINK) and hold.

ATIS

119.1 269.9

CANNON APP CON

118.425 352.1

CANNON TOWER

120.4 270.25

GND CON

121.9 275.8

CLNC DEL

120.2 293.225

CAUTION:

1. ILS Rwy 22 Height Group 4 WCH 19 feet.

† Missed approach requires use of RNAV or ATC RADAR monitoring.

CVS 17 003° 183° 265K 10,000 7000 HOLD

(IAF) HEDOB CVS 12 6000 CVS 12 Arc LR-027 038° (IF) HEKDI CVS 12

4753

4443 4475 4634 4500 4659

CANNON Chan 53 CVS

JEBES CVS 6 R-220 R-193

LOCALIZER 109.7 I-CVS

CLINK CVS 12 013° 265K 10,000 7000 HOLD

CVS 17

OPKUE CVS 5.1

MSA CVS 2.5 NM 6600

EMERG SAFE ALT 100 NM 8000

6000 CVS R-220

JEBES CVS R-220 6

7000

CLINK CVS R-193 12

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 38).

HEDOB R-003 12 7000

HEKDI 12 6000

Arc 12

GS 3.00° TCH 44

5600

218°

4 NM

TACAN LOC MAP 1.2 2.4

CATEGORY	A	B	C	D	E
S-ILS 22*	4495/24		200	(200-½)	
S-LOC 22**	4720/24 425 (500-½)		4720/40 425 (500-¾)		
CIRCLING	4840-1 545 (600-1)		4860-1½ 565 (600-1½)	5000-2¼ 705 (800-2¼)	5020-2½ 725 (800-2½)

CLOVIS, NEW MEXICO

34°23'N-103°19'W

Amtdt 4 13AUG20

CANNON AFB (KCVS)

ILS or LOC RWY 22

ELEV 4295

TDZE 4295

4433 TWR 4437

10,003 x 150

81.96 x 150 0.3% UP

3.1

A3 A1 P

218°

HIRL all rwy's

FAF to MAP 4 NM

Knots	60	90	120	150	180
Min:Sec	4:00	2:40	2:00	1:36	1:20

SW-1, 18 MAY 2023 to 15 JUN 2023

SW-1, 18 MAY 2023 to 15 JUN 2023