

VOR/DME MML

111.0

Chan 47

APP CRS

130°

Rwy Idg

7221

TDZE

1183

Apt Elev

1183

SOUTHWEST MINNESOTA RGNL MARSHALL/RYAN FLD (MML)

VOR RWY 12

NA

For inop ALS, increase S-12 Cat C/D visibilities to 1½ SM, CEGUL fix minimums: S-12 Cat C/D visibility to 1 SM. For inop ALS when using Tracy altimeter setting increase S-12 Cat C/D visibilities to 1¾ SM. When local altimeter setting not received, use Tracy Muni altimeter setting and increase all MDAs 60 feet, S-12 Cat C/D visibility ½; Circling Cat C/D visibility ¼ SM; CEGUL fix minimums: increase Circling C/D visibility ¼ SM. VDP NA when using Tracy Muni altimeter setting.

MALSR

MISSED APPROACH: Climb to 2000, then climbing left turn to 2800 direct MML VOR/DME and hold.

AWOS-3PT 120.150	MINNEAPOLIS CENTER 127.1 290.2	GCO 121.725	UNICOM 122.8 (CTAF)
---------------------	-----------------------------------	----------------	------------------------

Remain within 10 NM		VOR/DME 6000		2000	2800	MML					
CEGUL MML 3		MML 1.9		1760	130° to VOR/DME						
1.1 NM		1.1 NM									
CATEGORY	A	B	C	D							
S-12	1760-½ 577 (600-½)		1760-1¼ 577 (600-1¼)								
CIRCLING	1760-1 577 (600-1)		1820-1¾ 637 (700-1¾)		1840-2 657 (700-2)						
CEGUL FIX MINIMUMS											
S-12	1560-½ 377 (400-½)		1560-¾ 377 (400-¾)								
CIRCLING	1640-1 457 (500-1)		1820-1¾ 637 (700-1¾)		1840-2 657 (700-2)						
					HIRL Rwy 12-30						
					REIL Rws 2 and 20						
					MRL Rwy 2-20						

MARSHALL, MINNESOTA

Amdt 8C 15JUL21

SOUTHWEST MINNESOTA RGNL MARSHALL/RYAN FLD (MML)

44°27'N-95°49'W

VOR RWY 12