

WAAS CH 99407 W18B	APP CRS 176°	Rwy Idg 13400 TDZE 606 Apt Elev 606	RNAV (GPS) RWY 18R DALLAS-FORT WORTH INTL (DFW)
--	------------------------	--	---

RADAR required for procedure entry. RNP APCH.

Simultaneous approach authorized with Rwy 17L/C/R. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C or above 54°C. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000 and LNAV Cats C and D visibility to 1¼ SM.

ALS-2

MISSED APPROACH:
Climb to 1100 then climbing right turn to 3000 direct LIKES and hold.

D-ATIS ARR 123.775 DEP 135.925	REGIONAL APP CON 118.425	DFW TOWER 126.55 EAST 124.15 WEST	GND CON 121.65 EAST 121.85 WEST	CLNC DEL 128.25	CPDLC
--	------------------------------------	---	---	---------------------------	-------

ELEV 606	D	TDZE 606
176°		
*LNAV only.		
*1.7 NM to RWY18R		
RWY18R		
1.7 NM 3.8 NM 2.1 NM 6.3 NM 3.2 NM		
CATEGORY	A	B C D
LPV DA	806/18 200 (200-½)	
LNAV/VNAV DA	1012/40 406 (500-¾)	
LNAV MDA	1220/24 614 (700-½)	1220-1¾ 614 (700-1¾)

DALLAS-FORT WORTH, TEXAS
Amdt 1C 22APR21

32°54'N-97°02'W

DALLAS-FORT WORTH INTL (DFW)
RNAV (GPS) RWY 18R