

WAAS CH 45805 W35B	APP CRS 356°	Rwy Idg 13400 TDZE 564 Apt Elev 607
--	------------------------	--

RNAV (GPS) RWY 35L

DALLAS-FORT WORTH INTL (DFW)

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C (25°F) or above 54°C (130°F). Simultaneous approach authorized with Rwy 36L/R and Rwy 35R.
DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH:

Climb to 3000 direct BBAKR and on track 357° to BOSSI and hold.

D-ATIS ARR 123.775 DEP 135.925	REGIONAL APP CON 127.075	DFW TOWER 126.55 EAST 124.15 WEST	GND CON 121.65 EAST 121.85 WEST	CLNC DEL 128.25	CPDLC
--	------------------------------------	---	---	---------------------------	-------

RADAR REQUIRED

MISSED APCH FIX

MSA RW35L 25 NM

TANDE		CORMN		DALLN		BEGGO		BBAKR		BOSSI		
6000		5000		3000		2300		tr 357°		△		
GP 3.00° TCH 47						*1.2 NM to RW35L						
3.2 NM		6.3 NM		2.4 NM		4.1 NM		1.2				
CATEGORY	A	B		C		D						
LPV DA	764/18		200 (200-½)									
LNAV/VNAV DA	928/40		364 (400-¾)									
LNAV MDA	1020/24		456 (500-½)		1020/45		456 (500-¾)					

ELEV 607

HIRL all Rwys
REIL Rwy 13L and 31L
TDZ/CL all Rwys except 13L, and 31L

DALLAS-FORT WORTH, TEXAS

Amcl 2B 17AUG17

32°54'N-97°02'W

DALLAS-FORT WORTH INTL (DFW)

RNAV (GPS) RWY 35L