

WAAS

CH **86233**

W26A

APP CRS

264°

Rwy Idg

5004

TDZE

176

Apt Elev

176

RNAV (GPS) RWY 26

CAMILLA-MITCHELL COUNTY (CXU)

NA

Baro-VNAV NA when using Albany altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Albany altimeter setting and increase LPV DA to 553 feet; increase LNAV/VNAV DA to 601 feet; increase all MDAs 60 feet and LNAV Cats C/D and Circling Cat D visibility ¼ SM. Rwy 26 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:

Climb to 2200 direct CEGUK and hold.

AWOS-3T 118.675	JACKSONVILLE CENTER 125.75 363.075	UNICOM 122.8 (CTAF) 0
---------------------------	--	--

ELEV 176

TDZE 176

2200

CEGUK

264°

221±

5004 X 100

264°

26

1.4 NM

3.8 NM

6.1 NM

2400

084°

264°

GP 3.00° TCH 58

4 NM Holding Pattern

CEVOR

KUBCE

1900

1900

1.4 NM to RW26

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 39).

CEVOR

4 NM Holding Pattern

CATEGORY	A	B	C	D
LPV DA	505-1		329 (400-1)	
LNAV/VNAV DA	553-1¼		377 (400-1¼)	
LNAV MDA	660-1	484 (500-1)	660-1¾	484 (500-1¾)
CIRCLING	720-1 544 (600-1)	760-1 584 (600-1)	920-2¼ 744 (800-2¼)	940-2½ 764 (800-2½)

REIL Rwy 8 and 26 **0**

MIRL Rwy 8-26 **0**

CAMILLA, GEORGIA

Amdt 1D 21APR22

31°13'N-84°14'W

CAMILLA-MITCHELL COUNTY (CXU)

RNAV (GPS) RWY 26