

|                                        |                        |                                                            |
|----------------------------------------|------------------------|------------------------------------------------------------|
| WAAS<br>CH <b>97404</b><br><b>W08B</b> | APP CRS<br><b>092°</b> | Rwy Idg <b>10506</b><br>TDZE <b>9</b><br>Apt Elev <b>9</b> |
|----------------------------------------|------------------------|------------------------------------------------------------|

RNAV (GPS) Z RWY 8R

MIAMI INTL (MIA)

|                                                                                                                                                                                                                                                                                                          |           |                                                                                        |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|----------------------------------------------------------------------------------------|
| RNP APCH.<br>▼ Rwy 8R helicopter visibility reduction below RVR 4000 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 8°C or above 54°C. For inop ALS, increase LPV all Cats visibility to RVR 4500, LNAV/VNAV Cats C and D visibility to 1½ SM and LNAV Cats A and B visibility to RVR 5500. | MALSR<br> | MISSED APPROACH: Climb to 3000 direct EWKIF and on track 127° to VKZ VOR/DME and hold. |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|----------------------------------------------------------------------------------------|

|                                                   |                                      |                                   |                                                                      |              |                           |       |
|---------------------------------------------------|--------------------------------------|-----------------------------------|----------------------------------------------------------------------|--------------|---------------------------|-------|
| D-ATIS<br>ARR <b>119.15</b><br>DEP <b>133.675</b> | MIAMI APP CON<br><b>124.85 322.3</b> | MIAMI TOWER<br><b>118.3 256.9</b> | GND CON<br><b>121.8</b> (8L/8R/12/26L/26R)<br><b>127.5</b> (9/27/30) | <b>348.6</b> | CLNC DEL<br><b>135.35</b> | CPDLC |
|---------------------------------------------------|--------------------------------------|-----------------------------------|----------------------------------------------------------------------|--------------|---------------------------|-------|

