

SW-3, 07 SEP 2023 to 05 OCT 2023

**TOP ALTITUDE:**  
6000


NOTE: RADAR required.

NOTE: RNAV 1.

NOTE: DME/DME/IRU or GPS required.

NOTE: This procedure not authorized for turbojet aircraft.

JOHN WAYNE TOWER\*  
126.8 343.625  
SOCAL DEP CON  
125.35 316.125



**TAKEOFF MINIMUMS**  
Rwys 2R, 20L: NA-ATC.  
Rwy 2L: Standard.  
Rwy 20R: Standard with minimum climb  
of 270' per NM to 1300.

NOTE: Chart not to scale.

**DEPARTURE ROUTE DESCRIPTION**

**TAKEOFF RUNWAY 2L:** Climb heading 014° to 560, then left turn on heading 240° or as assigned by ATC for vectors to PIJIN, cross PIJIN at or above 4000, then on track 290° to cross HAWWC at or above 5000, thence . . . .

**TAKEOFF RUNWAY 20R:** Climb heading 194°, then on heading 210° or as assigned by ATC for vectors to PIJIN, cross PIJIN at or above 4000, then on track 290° to cross HAWWC at or above 5000, thence . . . .

. . . . on (transition). Maintain 6000. Expect higher altitude 10 minutes after departure.

**IKAYE TRANSITION (HAWWC3.IKAYE)**

SW-3, 07 SEP 2023 to 05 OCT 2023