


WAAS CH 40002 W21A	APP CRS 208°	Rwy Idg TDZE Apt Elev	7619 4977 5045
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 21L

PRESCOTT RGNL-ERNEST A LOVE FLD (P.R.C)

RNP APCH - GPS.				MALSR		MISSED APPROACH: Climb to 5500 then climbing right turn to 9100 direct DILLY and hold, continue climb-in-hold to 9100.	
⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C or above 47°C. For inoperative ALS, increase LPV all Cats visibility to 1 SM, LNAV/VNAV all Cats visibility to 1½ SM, and LNAV Cat C/D visibility to 1¾ SM. Circling Rwy 3L, 12, 30 NA at night. # Missed approach requires a minimum climb of 345 feet per NM to 7300.							
ATIS 127.2	PHOENIX APP CON 133,575 281.55	PRESCOTT TOWER * 125.3 (CTAF) 257.9	GND CON 121.7	CLNC DEL 119.25	128.75 (12-30) 125.3 (CTAF) (3R-21L)	UNICOM 122.95	



ELEV 5045	D	TDZE 4977
-----------	----------	-----------



5500	9100	DILLY				
↑	↷	△				
*LNAV only.			ZIPAK 2.2 NM to RW21L	HUMTY 7900	PEVYU	7 NM Holding Pattern
			*1.5 NM to RW21L			
			RW21L	7900	9100	GP 3.00° TCH 55
			1.5	0.7	6.9 NM	8.3 NM

CATEGORY	A	B	C	D
LPV DA	# 5177-½ 200 (200-½)			
LPV DA	5277-½ 300 (300-½)			
LNAV/VNAV DA	5391-¾ 414 (400-¾)			
LNAV MDA	5480-½ 503 (500-½)	5480-1 503 (500-1)		
C CIRCLING	5520-1 475 (500-1)	5760-1 715 (800-1)	6080-3 1035 (1100-3)	6680-3 1635 (1700-3)

PRESCOTT, ARIZONA
MIRL Rwy 12-30
REIL Rwy 3R, 12, and 30

PRESCOTT RGNL-ERNEST A LOVE FLD (P.R.C)
RNAV (GPS) RWY 21L

34°39'N-112°25'W

SW-4, 07 SEP 2023 to 05 OCT 2023

SW-4, 07 SEP 2023 to 05 OCT 2023