


WAAS CH 62914 W04A	APP CRS 044°	Rwy Idg 10701 TDZE 1057 Apt Elev 1077
--	------------------------	--

RNAV (GPS) RWY 4L

WILMINGTON AIR PARK (ILN)

RNP APCH.				MALSR		MISSED APPROACH: Climb to 3000 direct WIZRD and hold.
	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. For inop ALS, increase LNAV Cats A/B visibility to RVR 5500 and LNAV Cats C/D visibility to RVR 6000. *1800 RVR authorized with use of FD or AP or HUD to DA.					
D-ATIS 124.925	COLUMBUS APP CON 118.85 269.275	WILMINGTON TOWER ★ 119.475 (CTAF) 0	GND CON 121.6	CLNC DEL 128.85		



4 NM Holding Pattern		CHMLE	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 62).		3000 ↑	WIZRD ✦
6000 3000	← 224° 044° →	LYMEE	JAYEL 1.8 NM to RW04L	1680	1.1 NM to RW04L	RW04L
GP 3.00° TCH 51			2800			
			6.1 NM 3.5 NM 0.7 1.1 NM			
CATEGORY	A	B	C	D		
LPV DA *	1257/24		200 (200-½)			
LNAV/ VNAV	DA	1505/45		448 (500-¾)		
LNAV MDA	1460/24	403 (400-½)	1460/40	403 (400-¾)		
CIRCLING	1540-1	463 (500-1)	1860-2¼ 783 (800-2¼)	1860-2½ 783 (800-2½)		

