


WAAS CH 72605 W32A	APP CRS 319°	Rwy Idg TDZE 27 Apt Elev 30
--	------------------------	---


RNAV (GPS) RWY 32

SARASOTA/BRADENTON INTL (SRQ)

RNP APCH. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 43°C. When control tower closed, LPV and LNAV/VNAV NA; increase LNAV all Cats visibility to 1 mile. When control tower closed, inop table does not apply to LNAV Cats A and B. When control tower closed, for inop MALSR, increase LNAV Cat C and D visibility to 1½ mile.			MALSR 	MISSED APPROACH: Climb to 3000 direct ACIPU and on track 047° to PAIRS and hold, continue climb-in-hold to 3000.	
ATIS 124.375	TAMPA APP CON 119.65 353.575	SARASOTA TOWER ★ 120.1(CTAF) 0 256.8	GND CON 121.9 273.6	CLNC DEL 118.25	UNICOM 122.95



ELEV 30	D	TDZE 27
---------	----------	---------



3000 ↑	ACIPU ✱	tr 047° ↑	PAIRS △	FAXID 4 NM Holding Pattern	
*LNAV only.		ZALDI 1.5 NM to RW32	RINGY 1800	139° → ← 319°	2000
RW32		540*	1800	GP 3.00° TCH 53	
1.5 NM		3.9 NM	6 NM		
CATEGORY	A		B	C	D
LPV DA	227-½ 200 (200-½)				
LNAV/ VNAV DA	463-1 436 (500-1)				
LNAV MDA	440-½	413 (500-½)	440-¾	413 (500-¾)	
CIRCLING	500-1	470 (500-1)	600-1½ 570 (600-½)	600-2 570 (600-2)	

SE-3, 07 SEP 2023 to 05 OCT 2023

SE-3, 07 SEP 2023 to 05 OCT 2023