

WAAS CH 77617 W09A	APP CRS 090°	Rwy Idg TDZE 96 Apt Elev 112
--	------------------------	--

RNAV (GPS) RWY 9

ESLR RGNL (ESTF')

RNP APCH-GPS.


▼

⚠


Circling Rwy 14, 32 NA at night. Baro-VNAV and VDP NA when using Alexandria Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C or above 54°C. When local altimeter setting not received, use Alexandria Intl altimeter setting: increase LPV DA to 331 feet; increase LNAV/VNAV DA to 644 feet and all visibility ¼ SM; increase all MDAs 40 feet and Circling visibility Cat D ¼.

MISSED APPROACH: Climb to 3000 direct ILULE and hold.

ESF ASOS 119.425	POLK APP CON 125.4 254.8	UNICOM 122.8 (CTAF) 0
----------------------------	------------------------------------	---------------------------------



ELEV 112	D	TDZE 96
-----------------	----------	----------------



4 NM Holding Pattern				JEVOB	ICIVI	HOLAB	RW09
2000				270°	090°	1700	090°
GP 3.00° TCH 53				6.5 NM	2.4 NM	1.2 NM	1.3 NM
CATEGORY	A	B	C	D			
LPV DA	296-3¼			200 (200-¾)			
LNAV/VNAV DA	609-1¾			513 (500-1¾)			
LNAV MDA	560-1	464 (500-1)	560-1¾	464 (500-1¾)			
CIRCLING	600-1	488 (500-1)	740-1¾	628 (700-1¾)	760-2	648 (700-2)	