

LOC I-FSM	APP CRS	Rwy ldg	9318
111.3	260°	TDZE	448
		Apt Elev	469

ILS Z or LOC Z RWY 26

FORT SMITH RGNL (FSM)

DME required.

⚠

Circling NA for Cat E when R-2401B active. Circling NA for Cat E northwest of Rwy 8 and 20. For inop ALS, increase S-ILS 26 Cat E visibility to RVR 4000 and S-LOC 26 Cat C/D/E to 1½ SM. Circling Rwy 20, 26 NA at night. *RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 1400 then climbing left turn to 4000 on heading 224° and FSM VORTAC R-232 to SPIRO/FSM 15 DME and hold, continue climb-in-hold to 4000.

ATIS	RAZORBACK APP CON	FORT SMITH TOWER	GND CON	CLNC DEL	UNICOM
126.3	120.9 343.75	118.3 (CTAF) 323.175	121.9 275.8	133.85 278.3	122.95

MSA FSM 25 NM

090° 270°

4500 3900

LOC 111.3 I-FSM

1993 1080 888 1047 769 716 661± 827 892 891 (IAF) UXADY 1055

FORT SMITH 110.4 FSM Chan 41

WIZER INT RADAR

OCEXA FSM 10

LR-076 LR-100

R-2401B R-2401A R-2402A R-2402B R-2402C

FSM 10 Arc 3100

FSM 15 SPIRO

052° 232°

NA when R-2401 or R-2402 is active.

ELEV 469 TDZE 448

1400 4000

FSM R-232 SPIRO

hdg 224°

WIZER INT RADAR

2700

260°

3100

GS 3.00° TCH 50

6.9 NM 7.1 NM

CATEGORY A B C D E

S-ILS 26* 648/24 200 (200-½)

S-LOC 26 960/24 512 (500-½) 960/55 512 (500-1)

CIRCLING 1140-1 671 (700-1) 1400-2¾ 931 (1000-2¾) 1400-3 931 (1000-3)

HIRL Rwy 8-26 MIRL Rwy 2-20

FAF to MAP 6.9 NM

Knots 60 90 120 150 180

Min:Sec 6:54 4:36 3:27 2:46 2:18

FORT SMITH, ARKANSAS

Amdt 23 15JUN23

35°20'N-94°22'W

FORT SMITH RGNL (FSM)

ILS Z or LOC Z RWY 26