

LOC I-AEG	APP CRS	Rwy Idg	7398
110.1	215°	TDZE	5817
		Apt Elev	5837

ILS or LOC RWY 22

DOUBLE EAGLE II (AEG)

⚠


NA

When local altimeter setting not received, use Albuquerque Intl Support altimeter setting and increase all DA 94 feet, increase all MDA 100 feet, and increase visibility S-LOC 22 Cats C/D ¼ mile, Circling Cats C/D ½ mile. For inop MALSR when using Albuquerque Intl Support altimeter setting, increase visibility S-ILS 22 all Cats ¾ mile.

MALSR

MISSED APPROACH: Climb to 6500 then climbing right turn 7700 direct DUDLE LOM and hold.

ATIS	ALBUQUERQUE APP CON	DOUBLE EAGLE II TOWER ★	GND CON	CLNC DEL
119.025	127.4 253.5	120.15 (CTAF) 0	121.625	124.8 (When twr closed)



REIL Rwy 17 and 35 0				
MIRL Rwy 4-22 and 17-35 0				
FAF to MAP 5.5 NM				
Knots	60	90	120	150 180
Min:Sec	5:30	3:40	2:45	2:12 1:50
CIRCLING				
	6400-1	563 (600-1)	6420-1½	6640-2½
			583 (600-1½)	803 (900-2½)