

GLENDALE MUNI (GEU)(KGEU) 6 W UTC-7 N33°31.62' W112°17.71'

1071 B TPA—See Remarks NOTAM FILE GEU

RWY 01-19: H7150X100 (ASPH) S-40, D-60 MIRL 0.4% up NE

RWY 01: REIL. PAPI(P2L)—GA 3.0° TCH 38'. Thld displcd 701'.

Road. Rgt tfc.

RWY 19: REIL. PAPI(P2L)—GA 3.0° TCH 30'. Thld displcd 1001'.

Fence.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 01: TORA-7150 TODA-7150 ASDA-6980 LDA-6279

RWY 19: TORA-7150 TODA-7150 ASDA-7116 LDA-6115

SERVICE: S4 FUEL 100LL, JET A1+ OX 4 LGT When twr clsd

ACTIVATE REIL Rwy 01 and Rwy 19, PAPI Rwy 01 and Rwy 19,

MIRL Rwy 01-19—CTAF.

NOISE: Touch and go ldg discouraged between 0500-1300Z. Avoid noise sensitive area N and SE; noise abatement proc - amgr. Rwy 01 preferred for noise abatement.

AIRPORT REMARKS: Attended 1330-0230Z. Fuel: 100LL self serv avbl H24. Jet A 1330-0230Z; fee aft hr — 623-877-3333. Mil jet tfc 5 miles west. Coyotes and birds on and invof arpt. Unmkd and unlgt pw lines 1/4 mile west parallel to rwy. TPA-2101(1030), 1701(630) helicopter/ultralights, 2601(1530), high performance. Helicopter pattern not authorized SS-SR.

AIRPORT MANAGER: 623-930-4744

WEATHER DATA SOURCES: AWOS-3 (623) 877-8609

COMMUNICATIONS: CTAF 121.0 ATIS 119.425 UNICOM 122.95

PHOENIX RCO 122.2 (PRESCOTT RADIO)

® **LUKE APP/DEP CON** 118.15 (North) (1300-0530Z Mon-Thu, 1300-0130Z Fri, clsd wkend, hol and AETC family days).

® **PHOENIX APP/DEP CON** 120.7 (0530-1300Z Tue-Fri; 0130Z Sat-1300Z Mon, H24 hol and AETC family days).

TOWER 121.0 (Mon-Fri 1300-0330Z, Sat-Sun 1400-0200Z) **GND CON** 118.0

CLEARANCE DELIVERY PHONE: For CD when ATCT clsd, ctc Phoenix Apch at 602-306-2565.

AIRSPACE: CLASS D svc 1300-0330Z Mon-Fri, 1400-0200Z Sat-Sun; other times CLASS G.

RADIO AIDS TO NAVIGATION: NOTAM FILE PRC.

PHOENIX (H) VORTACW 115.6 PXR Chan 103 N33°25.98' W111°58.21' 277° 17.2 NM to fld. 1184/12E.

VOR unusable:

000°-015° byd 33 NM blo 11,000'

015°-034° byd 33 NM blo 10,000'

090°-100° byd 15 NM blo 8,000'

185°-190° byd 30 NM blo 8,000'

185°-190° byd 38 NM blo 9,000'

190°-230° byd 20 NM blo 10,000'

345°-000° byd 33 NM blo 10,000'

345°-034° byd 10 NM blo 6,000'

345°-034° byd 20 NM blo 8,000'

TACAN AZIMUTH unusable:

000°-015° byd 33 NM blo 11,000'

015°-034° byd 33 NM blo 10,000'

090°-100° byd 15 NM blo 8,000'

185°-190° byd 30 NM blo 8,000'

185°-190° byd 38 NM blo 9,000'

190°-230° byd 20 NM blo 10,000'

345°-000° byd 33 NM blo 11,000'

345°-034° byd 10 NM blo 6,000'

345°-034° byd 20 NM blo 8,000'

DME unusable:

000°-015° byd 33 NM blo 11,000'

015°-034° byd 33 NM blo 10,000'

090°-100° byd 15 NM blo 8,000'

185°-190° byd 30 NM blo 8,000'

185°-190° byd 38 NM blo 9,000'

190°-230° byd 20 NM blo 10,000'

215°-315°

345°-000° byd 33 NM blo 11,000'

345°-034° byd 10 NM blo 6,000'

345°-034° byd 20 NM blo 8,000'

COMM/NAV/WEATHER REMARKS: Emergency frequency 121.5 not monitored by twr.

PHOENIX

H-4J, L-5B, A

IAP, AD

