


LOC/DME I-HKH 111.5 Chan 52	APP CRS 047°	Rwy Idg TDZE 619 Apt Elev 620	ILS or LOC RWY 4R CHICAGO MIDWAY INTL (MDW)		
---	------------------------	---	--	--	--

- RNAV 1-GPS or RADAR required for procedure entry.
DME required for LOC only.
- ▼ Circling Rwy 31R NA at night.

▲ Rwy 4R helicopter visibility reduction below RVR 4000 NA.
- MISSED APPROACH: Climb to 1100 then climbing right turn to 2100 on heading 230° and on EON VORTAC R-001 until crossing IGECY INT/EON 20 DME, then climb to 2600 to EON VORTAC and hold.

D-ATIS 132.75	CHICAGO APP CON 128.2 353.875	MIDWAY TOWER 135.2 269.125	GND CON 118.075	CLNC DEL 124.625	CPDLC
-------------------------	---	--------------------------------------	---------------------------	----------------------------	-------



VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 66).				
ALQUE RADAR	BANER INT I-HKH 14.2	CADON INT I-HKH 10.8	CITGO I-HKH 5.6	OLOXE I-HKH 2.7
6000	5000	4000	2400	2400
GS 3.00° TCH 50	3.4 NM	3.4 NM	5.2 NM	2.9 NM
CATEGORY	A	B	C	D
S-ILS 4R	869/40	250 (300-¾)	869/50	250 (300-1)
S-LOC 4R	1000/55	381 (400-1)	1000/60	381 (400-1¼)
◼ CIRCLING	1120-1	500 (500-1)	1340-2 720 (800-2)	1340-2¼ 720 (800-2¼)