

WAAS
CH **93643**
W29A

APP CRS
296°

Rwy Idg
TDZE
Apt Elev

7250
480
501

RNAV (GPS) RWY 29

LOUISVILLE MUHAMMAD ALI INTL (SDF)

▽

▲

Circling Rwy 11 NA at night. Rwy 29 helicopter visibility reduction below RVR 4000 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LPV all Cats visibility and LNAV Cats A/B visibility to RVR 5000.

MALS

AS

MISSED APPROACH:

Climb to 3000 direct ZUSAB and on track 269° to DAMEN and hold.

D-ATIS 118.725	LOUISVILLE APP CON 132.075 327.0	LOUISVILLE TOWER 124.2 257.8	GND CON 121.7 348.6	CLNC DEL 126.1 275.8	CPDLC
--------------------------	--	--	-------------------------------	--------------------------------	-------

MISSED APCH FIX

099°

279°

4 NM

Procedure NA for arrivals at FINCH on V512 eastbound.

Procedure NA for arrivals at MIXKO on V51 southbound.

MSA RW29 2.5 NM

3600

ELEV 501	D	TDZE 480
----------	----------	----------

HIRL all Rwy
TDZ/CL Rwy 17L,
35R, 17R, and 35L

3000	ZUSAB	tr 269°	DAMEN	4 NM Holding Pattern
*LNAV only.				
CUCAK 2200				
RW29 1.6 3.6 NM 6 NM				
CITMO	116° 10000 3000			
GP 3.00° TCH 55				
CATEGORY	A	B	C	D
LPV DA	773/40 293 (300-¾)			
LNAV/VNAV DA	943/50 463 (500-1)			
LNAV MDA	1040/40	560 (600-¾)	1040/50 560 (600-1)	1040/60 560 (600-1¼)
C CIRCLING	1040-1 539 (600-1)	1140-1 639 (700-1)	1160-1¾ 659 (700-1¾)	1400-3 899 (900-3)

LOUISVILLE, KENTUCKY

Orig-D 15AUG19

LOUISVILLE MUHAMMAD ALI INTL (SDF)

38°10'N-85°44'W

RNAV (GPS) RWY 29