

LOC/DME I-SSX <u>109.35</u> Chan 30 (Y)	APP CRS 201°	Rwy Idg 8000 TDZE 551 Apt Elev 599
---	------------------------	---

ILS or LOC/DME RWY 20L
NASHVILLE INTL (BNA)

T Simultaneous approach authorized with Rwy 20R.
A DME required.
 **RVR 1800 authorized with the use of FD or AP or HUD to DA.



MALS R



MISSED APPROACH: Climb to 1300 then climbing left turn to 3000 on heading 040° and BNA VORTAC R-072 to LENON/BNA 25.1 DME and hold.

D-ATIS 135.1	NASHVILLE APP CON 118.4 360.7	NASHVILLE TOWER 118.6 257.8	GND CON 121.9 348.6	CLNC DEL 126.05	CPDLC
-----------------	----------------------------------	--------------------------------	------------------------	--------------------	-------

RADAR REQUIRED



***LOC only.**

CATEGORY	A	B	C	D
S-ILS 20L	** 751/24 200 (200-½)			
S-LOC 20L	980/24	429 (400-½)	980/40	429 (400-¾)
C CIRCLING	1100-1 501 (600-1)	1120-1 521 (600-1)	1200-1¾ 601 (700-1¾)	1380-2½ 781 (800-2½)