

WAAS
CH **53404**
W13A

APP CRS
133°

Rwy Idg
TDZE **1731**
Apt Elev **1744**

RNAV (GPS) RWY 13

PIERRE RGNL (PIR)

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 45°C (113°F).
DME/DME RNP-0,3 NA.

MISSED APPROACH: Climb to 4000 direct HOGEX and hold.

ASOS 119.025	MINNEAPOLIS CENTER 125.1 269.1	CTAF 122.70	UNICOM 122.95
------------------------	--	-----------------------	-------------------------

ELEV 1744

D

TDZE 1731

4 NM Holding Pattern				4000 HOGEX	
GP 3.00° TCH 52				*LNAV only	
CATEGORY				A	
LPV DA				1981-¾ 250 (300-¾)	
LNAV/VNAV DA				2285-2 554 (600-2)	
LNAV MDA				2220-1 489 (500-1)	2220-1½ 489 (500-1½)
CIRCLING				2240-1 496 (500-1)	2460-2¼ 716 (800-2¼)

PIERRE, SOUTH DAKOTA

Amtd 2A 08OCT20

44°23'N-100°17'W

PIERRE RGNL (PIR)

RNAV (GPS) RWY 13