VALPARAISO, FLORIDA

ILS W or LOC W RWY 20

AL-436 [USAF] EGLIN AFB/DESTIN-FT WALTON BEACH (KVPS)

LOC/DME I-CAH	APCH CRS	Rwy ldg 10,001
109.1	192°	TDZE 63
Chan 28		Arpt Elev 84

DME, RADAR required for LOC approach.

* When ALS inop, increase RVR to 40 and vis to ¾ mile. When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile,
** CAT CDE RVR to 60 and vis to 1⅛ miles.

ALSF-1

MISSED APPROACH: Climb straight ahead to 3000 to CEW R-170/35 DME (MRCEE), then as directed by ATC.

ATIS *	APP CON	TOWER	GND CON	CLNC DEL
134.625 273.5	125.1 281.45 271°- 089° 132.1 360.6 090°- 270°	118.2 353.65	121.8 335.8	127.7 377.2

Procedure not usable at times due to restricted area activity.

R-286 286° 230K 106° 673 3000 108° (12.8) 012° R-012 (IAF) KANDE I-CAH 17 478 192° R-108 660 356 CITEY I-CAH 13 367 2300 466 1700 NELVE I-CAH 9 378 229° HVVVR I-CAH 7 191 339 WARRINGTON Chan 2 DWG MRCEE CEW 35 R-170 MSA DWG 25 NM 1800

IAF CRESTVIEW 115.9 CEW Chan 106

LOCALIZER 109.1 I-CAH Chan 28

EMERG SAFE ALT 100 NM 3600

ELEV 84 TDZE 63 192° 20 175 12 179 203 193 243 TWR 157 10,001 x 300 11,987 x 300 255 164 202 30 2

HIRL all rwys

† Rwy 20 apch lgt 1500′ nonstandard.

3000 LOC DME WEGDU I-CAH 2.3 I-CAH 3.1 HVVVR I-CAH 7 NELVE I-CAH 9 CITEY I-CAH 13 R-012 KANDE I-CAH 17 CEW VORTAC 192° 2300 1700 192° 3000 192° 3000 108° 3000 GS 2.80° TCH 59 0.5 NM 4.7 NM

LOC FAF to MAP 4.7 NM					
Knots	60	90	120	150	180
Min:Sec	4:42	3:08	2:21	1:53	1:34

CATEGORY	A	B	C	D	E
S-ILS 19 *	260/24		200	(200-½)	
S-LOC 19 **	480/24	420 (400-½)	480/40	420	(400-¾)
CIRCLING	660-1	576 (600-1)	760-2 676 (700-2)	760-2¼ 676 (700-2¼)	760-2½ 676 (700-2½)

SE-3, 30 NOV 2023 to 28 DEC 2023

SE-3, 30 NOV 2023 to 28 DEC 2023