

APP CRS

Rwy Idg

006°

6300

TDZE

6431

Apt Elev

6451

RNAV (RNP) Z RWY 1

JACKSON HOLE (JAC)

RNP AR APCH

▽

-22°C

For uncompensated Baro-VNAV systems, procedure NA below -27°C or above 54°C.
Inop table does not apply to RNP 0.11* all Cats visibility.
For inop ALS, increase RNP 0.30* all Cats visibility to ¾ SM.
Missed approach requires RNP less than 1.0.

MALS

⬮

A2

MISSSED APPROACH:

Climb to 14000 on track 007° to UBEVE and track 007° to QUIRT and track 088° to DNW VOR/DME and hold, continue climb-in-hold to 14000.
* Missed approach requires minimum climb of 330 feet per NM to 8200; if unable to meet climb gradient, see RNAV (RNP) Y RWY 1.

D-ATIS	SALT LAKE CENTER	JACKSON TOWER*	GND CON	UNICOM
120.625	133.25 285.6	118.075 (CTAF)	124.55	122.95

MISSSED APPROACH: Climb to 14000 on track 007° to UBEVE and track 007° to QUIRT and track 088° to DNW VOR/DME and hold, continue climb-in-hold to 14000.
* Missed approach requires minimum climb of 330 feet per NM to 8200; if unable to meet climb gradient, see RNAV (RNP) Y RWY 1.

ROUTING TO VUGUY (not to scale)
Procedure NA for arrivals at IDECA on V328 southeast bound.

Procedure NA for arrivals at OLNU on V465 southwest bound.

SEE INSET FOR ROUTING TO VUGUY

VUGUY

14000

006°

11600

GP 3.00°

TCH 50

LYET

11200

NECPI

10500

YONUL

9900

UBEVE

8600

QUIRT

8600

DNW

8600

JEVIM

8600

WIDGA

8600

RW01

8600

12 NM

2 NM

2.4

2.4

7.9 NM

6.7 NM

CATEGORY	A	B	C	D
RNP 0.11 DA*	6690-¾	259 (300-¾)		
RNP 0.30 DA*	6743-¾	312 (300-¾)		

AUTHORIZATION REQUIRED

ELEV 6451

TDZE 6431

CL Rwy 1-19

HIRL Rwy 1-19

TWR

6506

0.6% UP

6300 x 1.50

006°