


WAAS CH 45504 W24A	APP CRS 240°	Rwy Idg TDZE 115 Apt Elev 120
--	------------------------	---

RNAV (GPS) RWY 24
NORTHEAST PHILADELPHIA (PNE)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C (11°F) or above 54°C (130°F). DME/DME RNP-0.3 NA.	MALSRL	MISSED APPROACH: Climb to 900 then climbing right turn to 3000 direct ARD VOR/DME and hold.			
ATIS 121.15	PHILADELPHIA APP CON 123.8 291.7	NORTHEAST PHILADELPHIA TOWER ★ 126.9 (CTAF) 0 278.8	GND CON 121.7	CLNC DEL 127.25	UNICOM 122.95



900 3000 ARD	4 NM Holding Pattern			
* LNAV only	FLITS			
	BORDA			
	* 1.5 NM to RW24			
	RW24			
	240°			
	241°			
	2000			
	GP 3.00° TCH 53			
	1.5 4.3 NM 5.9 NM			
CATEGORY	A	B	C	D
LPV DA	315-½		200 (200-½)	
LNAV/VNAV DA	560-⅞		445 (500-⅞)	
LNAV MDA	640-½ 525 (600-½)		640-1 525 (600-1)	
CIRCLING	700-1 580 (600-1)		720-1½ 600 (600-1½) 780-2 660 (700-2)	

