

ILS or LOC RWY 25

LOC I-TYV
109.9

APCH CRS
252°

Rwy Idg 12,007
TDZE 301
Arpt Elev 312

AL-738 [USAF]

LITTLE ROCK AFB (KLRF)

RNP APCH: RNAV1 - GPS or RADAR required.

▲

*When TDZL/CL inop, increase RVR to 24. RVR 18 still authorized with use of FD, AP, or HUD to DA.
** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile, CAT CDE vis to 1½ miles.
*** Circling not authorized S of Rwy 7-25.

ALS-F-2
A

MISSED APPROACH: Climb to 900 then climbing right turn to 3000 direct HERCK and hold as published.

ALTERNATE MISSED APPROACH: Climbing to 3000 fly runway heading until LRF 2 DME, then turn right heading 360°, EFC from ATC.

ATIS ★
119.175 251.1

APP CON
119.5 306.2

TOWER
120.6 269.075

GND CON
132.8 275.8

CLNC DEL
253.5

4 NM

HOLD 4000
3000

HERCK

ATC RADAR required for holding above 4000' or greater than 200 KIAS.

JACKSONVILLE
Chan 29 LRF

Paired VHF/DME frequency 109.2

R2403A

R2403B

CAT E acft: RADAR required when R-2403 active

294

RW25

LOCALIZER 109.9
I-TYV

(IAF) AALII 230K

2000

1800

252°

(A)

HESUP LRF 6.1 RADAR

072°

230K

252°

072°

4 NM

HOLD 4000
2000

ATC RADAR required for holding above 4000' or greater than 230 KIAS.

MSA RW25 2.5 NM
3200

807

EMERG SAFE ALT 100 NM 4000

900

3000

HERCK

TACAN

SATEK LRF 2

LRF 2.8

HESUP LRF 6.1 RADAR

072°

252°

1800

4000

2000

GS 3.00°
TCH 56

0.5 NM

4.1 NM

CATEGORY

A

B

C

D

E

S-ILS 25*

501/18

200

(200-½)

S-LOC 25**

760/24

459 (500-½)

760/45

459 (500-¾)

CIRCLING ***

780-1
468
(500-1)

920-1
608
(700-1)

920-1¾
608
(700-1¾)

1040-2¼
728
(800-2¼)

1040-2½
728
(800-2½)

ELEV 312

TDZE 301

HIRL Rwy 07-25
TDZL/CL Rwy 25

FAF to MAP 4.1 NM

Knots

60

90

120

150

180

Min:Sec

4:06

2:44

2:03

1:38

1:22

SC-1, 30 NOV 2023 to 28 DEC 2023

SC-1, 30 NOV 2023 to 28 DEC 2023

JACKSONVILLE, ARKANSAS
Orig 07SEP23

34° 55' N-92° 09' W

LITTLE ROCK AFB (KLRF)

ILS or LOC RWY 25