


RNAV (GPS) RWY 22L
LAFAYETTE RGNL/PAUL FOURNET FLD (LFT)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). VDP NA with AcadiaNA Rgnl altimeter setting. When local altimeter setting not received use AcadiaNA Rgnl altimeter setting and increase all DA 29' feet and all MDA 40' feet; increase LNAV/VNAV visibility all Cats to RVR 3500, increase Circling visibility Cat C/D ½ SM. For inop MALSR, increase LNAV Cats C and D visibility ¾ mile. For inop MALSR, when using AcadiaNA Rgnl altimeter setting, increase LNAV/VNAV all Cats visibility to RVR 6000. Baro-VNAV NA when using AcadiaNA Rgnl altimeter setting.



BOZAN

2000 083° (18.1)

Procedure NA for arrivals at BOZAN on V222 southwest bound.

(IAF) KEBVE

2000 126° (8)

(IF) BEDDY

2000 306° (8)

(IAF) NEYID

2000 315° (16.4)

MYRIC

1041

564

284

230

192

RW22L

(FAF) JILEV

216° (11.9)

MISSED APCH FIX AYOTY

036° 216° 4 NM

MSA RW22L 25 NM

2900

ELEV 42

TDZE 38

216°

REIL Rwy 4L, 4R, 11, 22R and 29
MIRL Rwy 11-29 and 4L-22R
HIRL Rwy 4R-22L