

LOC/DME I-FNU 110.15 Chan 38 (Y)	APP CRS 275°	Rwy ldg 11002 TDZE 45 Apt Elev 55
--	------------------------	--


ILS or LOC RWY 27R
ORLANDO SANFORD INTL (SF'B)

▼ For inop ALS, increase PESIY FIX minimums
▲ Cat C/D visibility to 1 SM.

MALSR

MISSED APPROACH: Climb to 500 then climbing right turn to 2800 on heading 280° and ORL VORTAC R-355 to PAOLA INT/ORL 15.6 DME and hold, continue climb-in-hold to 2800.

ATIS 125.975	ORLANDO APP CON 135.3 351.9 (NORTH) 119.775 351.9 (SOUTH)	SANFORD TOWER★ 120.3 (CTAF) 0 254.35	GND CON 121.35 254.35	CLNC DEL 123.975	CLNC DEL 121.35 (when twr closed)
------------------------	---	---	---------------------------------	----------------------------	--



ELEV 55	D	TDZE 45	500	2800	PAOLA	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 72).
						UTIMY INT I-FNU [6.8]
			*LOC only.			UXFIM INT I-FNU [13.2]
			PESIY I-FNU [3.4]			One Minute Holding Pattern
			I-FNU [2]			GS 3.00° TCH 55
			1.4 NM			3.4 NM
			6.5 NM			
			CATEGORY			A
			S-ILS 27R			245-1/2 200 (200-1/2)
			S-LOC 27R			480-1/2 435 (500-1/2) 480-3/4 435 (500-3/4)
			CIRCLING			580-1 525 (600-1) 600-1 1/2 545 (600-1 1/2) 640-2 585 (600-2)
			PESIY FIX MINIMUMS			
			S-LOC 27R			400-1/2 355 (400-1/2) 400-5/8 355 (400-5/8)
			CIRCLING			580-1 525 (600-1) 600-1 1/2 545 (600-1 1/2) 640-2 585 (600-2)