

APP CRS
359°

Rwy Idg
TDZE
Apt Elev

5000
1321
1321

RNAV (GPS) RWY 36

FLOYD W JONES LEBANON (LBO)


▼

▲ NA

When local altimeter setting not received, use Springfield-Branson Ntl alritmeter setting: increase LNAV/VNAV DA to 1786 feet and all visibilities ½ SM; increase all MDAs 120 feet and LNAV visibility Cat C ⅔ SM, Cat D ½ and Circling visibility Cat C/D ½ SM. Baro-VNAV NA when using Springfield-Branson Ntl altimeter setting. Baro-VNAV NA below -17° C (1° F). DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 3500 direct ULIKY and hold.

AWOS-3PT 118.975	SPRINGFIELD APP CON 121.1 290.5	CLNC DEL 123.725	UNICOM 122.8 (CTAF) 0
---------------------	------------------------------------	---------------------	--------------------------



4 NM Holding Pattern

*LNAV only, VDP NA when using Springfield-Branson Ntl altimeter setting.

3500

ULIKY

GP 3.00° TCH 47

3500

179°

359°

359°

2700

6.7 NM

3.1 NM

1.1

RW36

*1.1 NM to RW36

CATEGORY	A	B	C	D
GLS PA DA	NA			
LNAV/VNAV DA	1680-1¼ 359 (400-1¼)			
LNAV MDA	1700-1 379 (400-1)		1700-1¼ 379 (400-1¼)	
CIRCLING	1820-1 499 (500-1)	1860-1 539 (600-1)	1980-1¼ 659 (700-1¼)	1980-2 659 (700-2)

REIL Rwy 18 and 36 0

MRL Rwy 18-36 0

