

WAAS
CH **40021**
W01A

APP CRS
009°

Rwy Idg
TDZE **1059**
Apt Elev **1077**

RNAV (GPS) RWY 1

RUTHERFORD COUNTY/MARCHMAN FLD (FQD)

Baro-VNAV NA when using Shelby-Cleveland County Rgnl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Shelby-Cleveland County Rgnl altimeter setting and increase all DA 77 feet, all MDA 80 feet, and increase LPV all Cats, LNAV/VNAV all Cats, LNAV Cats C/D and Circling Cats C/D visibility ¼ mile. VDP NA with Shelby-Cleveland County Rgnl altimeter setting.

MISSED APPROACH: Climb to 1700 then climbing left turn to 3000 direct EPOZI and hold.

AWOS-3 118.275	GREER APP CON ★ 119.4 350.2	UNICOM 122.8 (CTAF) 0
--------------------------	---------------------------------------	---------------------------------

Procedure NA for arrivals at SPA VORTAC on V605 southbound.

ELEV 1077
TDZE 1059
REIL Rwy 1
MIRL Rwy 1-19

4 NM Holding Pattern

EPOZI

JAKIB

CUVUG

RW01

3000

1700

3000

EPOZI

189°

009°

009°

292°

299°

GP 3.00°

TCH 40

*1700

*1 NM to RW01

*1 NM to RW01

6.9 NM

3.1 NM

0.9

1 NM

CATEGORY

A

B

C

D

LPV DA

1309-7⁵/₈

250 (300-7⁵/₈)

LNAV/VNAV DA

1459-13⁵/₈

400 (400-13⁵/₈)

LNAV MDA

1420-1

361 (400-1)

CIRCLING

1560-1
483 (500-1)

1620-1
543 (600-1)

1640-1¹/₂
563 (600-1¹/₂)

1820-2¹/₂
743 (800-2¹/₂)

RUTHERFORDTON, NORTH CAROLINA

RUTHERFORD COUNTY/MARCHMAN FLD (FQD)

Amdt 2A 22JUN17

35°26'N-81°56'W

RNAV (GPS) RWY 1