

WAAS CH 40426 W29A	APP CRS 291°	Rwy Idg TDZE Apt Elev	8900 7078 7096
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 29


RALPH WENZ FLD (P.N.A.)

⚠ Baro-VNAV NA. When local altimeter setting not received, use Big Piney altimeter setting and increase LPV DA to 7386 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 7664 feet and all visibilities ½ SM; increase all MDA 60 feet and LNAV Cats C/D visibility ¼ SM. Circling NA south of Rwy 11/29. DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. VDP NA with Big Piney altimeter setting.


ODALS

MISSED APPROACH: Climb to 7600 then climbing left turn to 10000 direct BPI VOR/DME and hold.

AWOS-3 118.325	SALT LAKE CENTER 128.35 239.25	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



ELEV 7096	TDZE 7078
-----------	-----------



7600	10000	BPI	VGSI and RNAV glidepath not coincident (VGSI Angle 2.83/TCH 40).		COTDA
*LNAV only.	*1.5 NM to RW29	PINIY	FEDPA	291°	9400
		8700	8700	8900	GP 3.00° TCH 55
	1.5 NM	3.5 NM	2.1 NM	5 NM	
CATEGORY	A	B	C	D	
LPV DA	7328-¾ 250 (300-¾)				
LNAV/ VNAV DA	7606-1¾ 528 (600-1¾)				
LNAV MDA	7600-1 522 (600-1)		7600-1½ 522 (600-1½)		
CIRCLING	7640-1 544 (600-1)		7840-2¼ 744 (800-2¼)		7980-3 884 (900-3)