

DENVER, COLORADO

AL-9077 (FAA)

23334

APP CRS	Rwy Idg	12000
353°	TDZE	5434
	Apt Elev	5434

RNAV (RNP) Z RWY 35L
DENVER INTL (DEN)

T

For uncompensated Baro-VNAV systems, procedure NA below -25°C (-13°F) or above 46°C (115°F). GPS required. For inoperative ALSF, increase RNP 0.10 all Cats visibility to RVR 4500 and RNP 0.30 all Cats visibility to RVR 5000. Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALSF-2



MISSED APPROACH: Climb to 10000, then right turn direct GLL VOR/DME and hold.


D-ATIS	DENVER APP CON			
ARR 125.6 379.9	119.3	307.3	120.35	379.3
DEP 134.025	(NORTH)		(SOUTH)	

DENVER TOWER
124.3 322.45

GND CON
121.85 377.1

CLNC DEL
118.75

CPDLC



MISSED APCH FIX

7 NM




△ 6529

RADAR REQUIRED

ELEV 5434	D	TDZE 5434
-----------	----------	-----------

HIRL all Rwys
TDZ/CL Rwys 7, 16L, 16R, 17R,
26, 34L, 34R, 35L, 35R



DYMOM

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).

10000



GLL

7000

RW35L

GP 3.00°
TCH 57

- 4.7 NM

CATEGORY	A	B	C	D
RNP 0.10 DA		5695/24	261 (300- $\frac{1}{2}$)	
RNP 0.30 DA		5760/32	326 (400- $\frac{5}{8}$)	

AUTHORIZATION REQUIRED

DENVER, COLORADO

Orig-C 01FEB18

DENVER INTL (DEN)

39°52'N-104°40'W

RNAV (RNP) Z RWY 35L

SW-1, 30 NOV 2023 to 28 DEC 2023