WAAS CH 72822 W03A	APP CRS 029°	Rwy ldg 6501 TDZE 246 Apt Elev 246

RNAV (GPS) RWY 3

RALEIGH EXEC JETPORT AT SANFORD-LEE COUNTY (TTA)

Baro-VNAV NA when using Raleigh/Durham altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Raleigh/Durham altimeter setting and increase all DA 81 feet and all MDA 100 feet. Increase LNAV/VNAV all Cats visibility to 1⅛ mile, LNAV Cats C and D visibility to 1 mile, and Circling Cat C visibility to 2 mile and Cat D visibility to 2¾ mile. For inop MALSR, increase LNAV/VNAV all Cats visibility to 1¼ mile and LNAV Cats C and D visibility to 1⅛ mile. For inop MALSR when using Raleigh/Durham altimeter setting, increase LPV all Cats visibility to ⅞ mile and LNAV Cats C and D visibility to 1⅜ mile. VDP NA when using Raleigh/Durham altimeter setting.

MALSR A5

MISSED APPROACH: Climb to 1300 then climbing left turn to 2100 direct IKTOW and hold.

AWOS-3	RALEIGH APP CON	UNICOM	GCO
120.625	125.3 353.675	123.075 (CTAF) L	135.075



ELEV	246	TDZE	246



CATEGORY		A	B	C	D
LPV	DA	446-½ 200 (200-½)			
LNAV/VNAV	DA	634-⅞ 388 (400-⅞)			
LNAV	MDA	660-½ 414 (500-½)		660-¾ 414 (500-¾)	
C CIRCLING		760-1 514 (600-1)	820-1 574 (600-1)	840-1½ 594 (600-1½)	960-2¼ 714 (800-2¼)

SE-2, 30 NOV 2023 to 28 DEC 2023

SE-2, 30 NOV 2023 to 28 DEC 2023