

CONTINUED FROM PRECEDING PAGE

RADIO AIDS TO NAVIGATION: NOTAM FILE ISP.

CALVERTON (L) (H) VORW/DME 114.55 CCC Chan 92(Y) N40°55.78' W72°47.93' 137° 9.2 NM to fld. 85/13W.

VOR unusable:

055°-075°

233°-268° byd 25 NM

269°-290°

DME unusable:

056°-066° byd 39 NM

SUFFOLK CO (T) TACAN Chan 47 FOK (111.0) N40°50.27' W72°37.91' at fld. 50/13W. NOTAM FILE FOK.

TACAN unmonitored when twr clsd.

No NOTAM MP: 1600-2000Z‡ Mon

TACAN AZIMUTH unusable:

028°-038° byd 8 NM blo 3,500'

090°-155° byd 7 NM

335°-345° byd 7 NM blo 3,500'

ILS/DME 111.7 I-FOK Chan 54 Rwy 24. Class IT. Unmonitored when ATCT clsd.

WHEELER-SACK AAF (GTB)(KGTB) A 1 NE UTC-5(-4DT) N44°03.34' W75°43.19'

690 B TPA—See Remarks NOTAM FILE GTB Not insp.

RWY 03-21: H1000X150 (CONC) PCN 59 R/B/W/T HIRL

RWY 03: ALSF1. PAPI(P4L)—GA 3.0° TCH 64'. RVR-TR Thld dsplcd 1363'.

RWY 21: ALSF1. PAPI(P4L)—GA 3.0° TCH 72'. RVR-TR Rgt ttc.

RWY 15-33: H5002X144 (CONC) PCN 43 R/C/W/T HIRL

RWY 15: MALSR. RVR-TR Rgt ttc.

RWY 08-26: H4501X150 (ASPH-CONC) PCN 34 F/A/W/T LIRL

RWY 08: Rgt ttc.

SERVICE: MILITARY— FUEL Service—L—AOE JASU-3(ASU600-270-DDP). Fuel A++ (mil); Avbl 1400-0300Z‡ Mon-Fri, Exc hol, OT PN. **FLUID SP** De-ice Type I and Type IV avbl with 3 hr PN. **TRAN ALERT:** Opr 1400-1300Z‡ Mon-Fri; clsd Sat, Sun and Federal Hol ltd; no cathering, lav, trash removal, water, or crew trnsp svc avbl.

NOISE: Service abatement Quiet hrs 0300-1100Z‡.

MILITARY REMARKS: Attended 1200-0300Z‡ Mon-Fri, clsd otr times PPR. Arpt clsd hols. See FLIP AP/1 Supplementary Arpt Information. Base Ops opr 1200-0400Z‡ Mon-Fri; clsd Sat, Sun and Federal Hol. All tran acct inbd for prk ctc Base Ops 20 min prior to ldg, mil aircrews must register with Base Ops if RON. Tran R/W prk south end of north ramp. Twy G, N, P, R and Twy L east of Twy B designated nonmovement area. Compass rose not calibrated. Acft inbd for Avn Fld Maint Act (AFMA) must arr no later 1900Z‡ ctc DSN 772-7536 C315-772-7536. Emerg ctc mt Ops cntr DSN 772-8620 C315-772-8620. **RSTD:** PPR ctc Base Ops DSN 772-5681, C315-772-5681/5682. Tenant acft have priority for ICl pat ops, tran may be ltd. Rwy 15-33. Twy G rstd to C130 or smaller. Sod ldg/ops rstd to cntr, sod. Oasis rst to tenant R/W hot refuel ops, ldg/dep prohibited when clsd. Oasis 4R-22L clsd N of point 4, dep 04R ldg, 22L prohibited. Twy B btn Twy A and N ramp clsd. **CAUTION** Extsy mil acft activity vcnty arpt mil acft refer to FLIP AP/1 prior to ops on Fort Drum or wi R5201. Narrow Twy A, B, int arc 40' wide. N Ramp edge lgt us. Twy B edge lgt us btn Twy A and Sabre helipad. W Ramp unlgtd. Oasis 22/04 Thld/end lgt us. Rsc not mntn when base ops is clsd. Wildlife haz, refer to AP/1. **TFC PAT** TPA—Rotary wing 1400(710), fixed wing 2000(1310), turbojet 2500(1810), overhead 3000(2310). **CSTMS/AG/IMG** No onsite cstms, consult FCG. Aerial port MSN acft plan arr btn 1300-0300Z‡ Mon-Fri exc hol, or rqr advanced coord and apvl. **MISC** Wx svc avbl 24/7. DSN 772-6065, C315-772-6065. Back-up wx brief avbl fr 15 OWS Scott AFB DSN 576-9755/9702, C618-256-9755/9702. Pri wx sensors automated H24. Drg augmentation/back-up wx observation pt is obst 033°-162°. PMSV freq not monitored Sat, Sun and federal hol. ATC will assist in cooperative watch by notifying wx of unprtd cond. Rwy 09-8-26 cntr 75' conc btn Rwy 03 and Twy D, PCN 54, remainder asph.

COMMUNICATIONS: ATIS 119.525④ **APP/DEP CON** 124.875 257.6**TOWER** 118.75 290.25 **GND CON** 121.9 229.8 **CLNC DEL** 121.9 **PMSV SACK METRO** 304.3**BASE OPS** 126.2 280.8 **FORT DRUM FLT FLW** 141.025 397.75**AIRSPACE:** CLASS D.

RADIO AIDS TO NAVIGATION: NOTAM FILE ART.

WATERTOWN (L) (L) VORTAC 109.8 ART Chan 35 N43°57.13' W76°03.88' 079° 16.2 NM to fld. 374/12W.

VOR unusable:

090°-111° byd 15 NM

112°-150°

151°-175° byd 20 NM

ILS/DME 108.5 I-AEZ Chan 22 Rwy 03.

ILS/DME 108.5 I-GTB Chan 22 Rwy 21. Class IE.

ASR/PAR

COMM/NAV/WEATHER REMARKS: Radar see Terminal FLIP for Radar Minima. 128.875 and 257.8 in all apch plates/mins.