

WAAS
CH **97741**
W04B


APP CRS
047°

Rwy Idg
TDZE **617**
Apt Elev **620**

RNAV (GPS) RWY 4L

CHICAGO MIDWAY INTL (MDW)

RNP APCH.				MISSED APPROACH: Climb to 1100 then climbing right turn to 2400 direct YIGUT and hold.	
Circding to Rwy 31R NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. Rwy 4L helicopter visibility reduction below ¾ SM NA.					
D-ATIS 132.75	CHICAGO APP CON 128.2 388.0	MIDWAY TOWER 135.2 269.125	GND CON 118.075	CLNC DEL 124.625	CPDLC



VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 39).		1100	2400	YIGUT
JERNU		HADGI	CEXUD	RW04L
2300		2300	2300	2300
GP 3.00°				
TCH 55				
4.9 NM		2.6 NM	1.2 NM	1.3 NM
CATEGORY	A	B	C	D
LPV DA	867-¾		250 (300-¾)	
LNAV/VNAV DA	1021-1½		404 (500-1½)	
LNAV MDA	1080-1 463 (500-1)		1080-1¾ 463 (500-1¾)	
CIRCLING	1120-1 500 (500-1)		1340-2 720 (800-2)	
			1340-2¼ 720 (800-2¼)	