

**TOP ALTITUDE:
ASSIGNED BY ATC**

D-ATIS
 120.0 254.3
 CLNC DEL
 125.0 379.1
 GND CON
 121.9 348.6
 EL PASO TOWER
 118.3 239.275
 EL PASO DEP CON
 119.15 263.0
 ALBUQUERQUE CENTER
 122.4 122.55

GREBE

SLNNK

FL180
 *9800
 004°
 (23)
 BOATY


FL180
 *12400
 304°
 (85)
 FL180
 *9800
 321°
 (47)

TAKEOFF MINIMUMS

Rwy 4: Standard with minimum climb of 500' per NM to 12400.

RUTER

17900
 *7200
 303°
 (19)



HBACK

FL180
 *17000
 265°
 (110)
 TELKE

FL180
 *17000
 271°
 (109)
 R-5115

SNTRS
14000

14000
 *9400
 305°
 (11)
 JCOXX
 263°
 13000
 *9400
 (8)

MRGEZ
13000

6450

042°

- NOTE: Takeoff Rwy 4, do not exceed 230K until passing 6450.
- NOTE: For use by Turbojet aircraft only.
- NOTE: RADAR required for non-GPS equipped aircraft.
- NOTE: DME/DME/IRU or GPS required.
- NOTE: RNAV 1.

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RWY 4: Climb heading 042° to 6450, then left turn direct JCOXX, thence. . .
 . . .(transition). Maintain altitude as assigned by ATC, expect filed altitude 10 minutes after departure.

- GREBE TRANSITION (JCOXX2.GREBE)
- HBACK TRANSITION (JCOXX2.HBACK)
- SLNNK TRANSITION (JCOXX2.SLNNK)
- TELKE TRANSITION (JCOXX2.TELKE)