


LOC/DME I-LLH	APP CRS	Rwy Idg	5001
111.55	265°	TDZE	36
Chan 52 (Y)		Apt Elev	36

ILS or LOC RWY 26

PHILADELPHIA INTL (PHL)

DME or RADAR required.		MALSR	MISSED APPROACH: Climb to 800 then climbing right turn to 3000 direct PTW VORTAC and hold.	
For inop ALS, increase S-ILS all Cats visibility to RVR 4500 and S-LOC Cats A and B visibility to RVR 5500 and Cat C to 1½ SM. Rwy 26 helicopter visibility reduction below RVR 4000 NA.				
D-ATIS	PHILADELPHIA APP CON	PHILADELPHIA TOWER		GND CON
ARR 133.4	124.35 319.15	118.5 327.05 (Rwys 9L/27R, 8/26 and 17/35)		121.9 348.6
DEP 135.925		135.1 327.05 (Rwy 9R/27L)		CLNC DEL 118.85 348.6



ELEV 36	D	TDZE 36
TDZ/CL Rwy 9R		
HIRL all Rwys		
REIL Rwys 9L and 35		
FAF to MAP 5.7 NM		
Knots	60	90 120 150 180
Min:Sec	5:42	3:48 2:51 2:17 1:54

800 3000 PTW		FOSOM I-LLH 8.4	
*LOC only.		ESKOE I-LLH 6.4	
(CFLFX) I-LLH 0.6		RADAR	
* I-LLH 2.5		2000	
265°		2000	
1.8 NM		3.9 NM	
2.1 NM		GS 3.15°	
TCH 50			
CATEGORY	A	B	C
S-ILS 26	299/40	263 (300-¾)	NA
S-LOC 26	700/40	664 (700-¾)	700-1½
			664 (700-1½)
			700-1⅞
			664 (700-1⅞)
CIRCLING	700-1	664 (700-1)	NA