


D-ATIS  
126.0  
CLNC DEL  
118.0  
CPDLC  
GND CON  
120.8  
JOHN WAYNE TOWER\*  
126.8 343.625  
SOCAL DEP CON  
125.35 316.125

NOTE: RADAR required.  
NOTE: RNAV 1.  
NOTE: DME/DME/IRU or GPS required.  
NOTE: This procedure not authorized for turbojet aircraft.



**TOP ALTITUDE:**  
6000

**DEPARTURE ROUTE DESCRIPTION**

**TAKEOFF RUNWAY 2L:** Climb heading 014° to 560, then left turn on heading 240° or as assigned by ATC for vectors to PIJIN, cross PIJIN at or above 4000, then on track 290° to cross HAWWC at or above 5000, thence . . . .

**TAKEOFF RUNWAY 20R:** Climb heading 194°, then on heading 210° or as assigned by ATC for vectors to PIJIN, cross PIJIN at or above 4000, then on track 290° to cross HAWWC at or above 5000, thence . . . .

. . . . on (transition). Maintain 6000. Expect higher altitude 10 minutes after departure.

**TAKEOFF MINIMUMS**  
Rwys 2R, 20L: NA-ATC.  
Rwy 2L: Standard.  
Rwy 20R: Standard with minimum climb of 270' per NM to 1300.

NOTE: Chart not to scale.

**IKAYE TRANSITION (HAWWC3.IKAYE)**