

APP CRS

191°

Rwy Idg

9500

TDZE

995

Apt Elev

1027

RNAV (RNP) Z RWY 19L


KANSAS CITY INTL (MCI)

RNP AR APCH - GPS.

MALSR

Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, procedure NA below -21°C or above 54°C. Simultaneous approach authorized, except for arrivals at ONEEL, BYKER, FARMS and BUDIE. For inop ALS, increase RNP 0.20 all Cats visibility to RVR 4500 and RNP 0.30 all Cats visibility to RVR 5500.

D-ATIS	KANSAS CITY APP CON	INTERNATIONAL TOWER	GND CON	CLNC DEL	CPDLC
128.375	120.95 318.1	128.2 254.25	121.8	135.7	



1500

4000

ANX

RWY 19L

JAZZE 2700

GP 3.00°

TCH 59

See planview for multiple IF locations.

5.2 NM

CATEGORY	A	B	C	D
RNP 0.20 DA		1310/24	315 (300-½)	
RNP 0.30 DA		1365/35	370 (400-⅔)	

AUTHORIZATION REQUIRED

HIRL all Rwws

TDZ/CL Rwws 1L, 1R, 19R and 19L