

LOM MF
372

APP CRS
323°

Rwy Idg
TDZE
Apt Elev
9001
1293
1297

NDB RWY 32

MANSFIELD LAHM RGNL (MFD)

▼

▲

RADAR required for procedure entry.

For inoperative ALS increase Cats A/B visibility to RVR 5500 and Cats C/D visibility to 1¾ SM.

MALSR

MISSED APPROACH: Climb to 2900 direct MFD VORTAC and hold.

ATIS 125.3	CLEVELAND APP CON ★ 124.2 360.65	MANSFIELD TOWER ★ 119.8 (CTAF) 291.775	GND CON 121.8 291.775	UNICOM 122.95
----------------------	--	--	---------------------------------	-------------------------

ELEV 1297

D

TDZE 1293

2900

MFD

MF LOM

Remain within 10 NM

2900

2700

3.16° TCH 50

4 NM

CATEGORY	A	B	C	D
S-32	1900/40	607 (700-¾)	1900-1¾	607 (700-1¾)
CIRCLING	1900-1	603 (700-1)	2000-2	2000-2¼
			703 (800-2)	703 (800-2¼)

MANSFIELD, OHIO
Amdt 11E 13SEP18

40°49'N-82°31'W

MANSFIELD LAHM RGNL (MFD)
NDB RWY 32

EC-2, 21 MAR 2024 to 18 APR 2024

EC-2, 21 MAR 2024 to 18 APR 2024