

APP CRS	Rwy Idg	10302
016°	TDZE	1314
	Apt Elev	1333

RNAV (RNP) Z RWY 1L

WICHITA DWIGHT D EISENHOWER NTL (ICT)

RNP AR APCH

Simultaneous approach authorized. Use of FD or AP providing RNAV track guidance required during simultaneous operations. For uncompensated Baro-VNAV systems, procedure NA below -15°C or above 54°C. For inop ALS, increase RNP 0.15 all Cats visibility to RVR 4500 and RNP 0.30 all Cats visibility to RVR 5500.

ALS F-2

MISSED APPROACH:
Climb to 4200 on track 016° to ACUBO and hold.

ATIS
125.15

WICHITA APP CON
126.7 353.5

WICHITA TOWER
118.2 257.8

GND CON
121.9 348.6

CLNC DEL
125.7

ELEV 1333 D TDZE 1314

HIRL all Rwys
REIL Rwys 14 and 32
TDZ/CL Rwy 1L

CATEGORY	A	B	C	D
RNP 0.15 DA		1626/28	312 (300-5%)	
RNP 0.30 DA		1676/35	362 (400-5%)	

AUTHORIZATION REQUIRED

NC-2, 21 MAR 2024 to 18 APR 2024

NC-2, 21 MAR 2024 to 18 APR 2024