



WAAS CH 97716 W27A	APP CRS 275°	Rwy Idg TDZE 72 Apt Elev 80	8003
--	------------------------	---	-------------

RNAV (GPS) RWY 27L

CECIL (VQQ)

RNP APCH.					MISSED APPROACH: Climb to 2000 direct ZORMI and hold.	
Rwy 27L helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.						
ATIS 125.275	JACKSONVILLE APP CON 127.775 377.075	CECIL TOWER★ 126.1 (CTAF) 235.625	GND CON 121.625 226.675	CLNC DEL 123.975 254.25	GCO 135.075	



2000

↑

ZORMI

✦

VGSI and RNAV glidepath not coincident (VGSI 3.00 Angle/TCH 67).

4 NM

Holding Pattern

JUZSO

095° →

6000

← 275°

2100

GP 3.00°

TCH 50

HATFI

1.8 NM to RW27L

OSTAF

1300

275°

680*

1300

*LNAV only.

*1 NM to RW27L

RW27L

1 NM

0.8 NM

1.9 NM

6.3 NM

CATEGORY	A	B	C	D
LPV DA	393-1		321 (400-1)	
LNAV/VNAV DA	451-1		379 (400-1)	
LNAV MDA	540-1	468 (500-1)	540-1⅓	468 (500-1⅓)
CIRCLING	540-1 460 (500-1)	560-1 480 (500-1)	600-1½ 520 (600-1½)	640-2 560 (600-2)