



WAAS CH 93601 W20A	APP CRS 206°	Rwy Idg TDZE Apt Elev	4410 955 957
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 20
DAYTON/WRIGHT BROTHERS (MGY)

RNP APCH.	MALS	MISSED APPROACH: Climb to 3100 direct SOVVO and hold.
▼ Inoperative table does not apply. When local altimeter setting not received, use James M Cox Dayton Intl altimeter setting and increase all DAs/MDAs 60 feet and Circling Cat C/D visibility ¼ SM. Rwy 20 helicopter visibility reduction below ¾ SM NA. VDP NA when using James M Cox Dayton Intl altimeter setting.		

ASOS 118.375	COLUMBUS APP CON 118.85 269.275	CLNC DEL 119.4	UNICOM 122.8 (CTAF) 0
------------------------	---	--------------------------	---------------------------------



3100	SOVVO	5 NM	WOBUL	Holding Pattern
* LNAV only.				
* 1.4 NM to RWY 20				
RWY 20				
TALAC				
2600				
3100				
GP 3.00°				
TCH 40°				
CATEGORY	A	B	C	D
LPV DA	1294-1¼ 339 (400-1¼)			
LNAV MDA	1440-1	485 (500-1)	1440-1¼	1440-1½
	523 (600-1¼)	563 (600-1¼)	485 (500-1¼)	485 (500-1½)
CIRCLING	1480-1¼	1520-1¼	1660-2	1660-2¼
	523 (600-1¼)	563 (600-1¼)	703 (800-2)	703 (800-2¼)