

LOC I-DPA 109.5	APP CRS 097°	Rwy Idg 4750 TDZE 756 Apt Elev 759
---------------------------	------------------------	---

ILS or LOC RWY 10


DUPAGE (DPA)

⚠

When local altimeter setting not received, use Chicago/Aurora altimeter setting: increase S-ILS 10 DA to 993 feet; increase all MDA 40 feet and visibility S-LOC 10 Cats C/D and HOVUB INT minimums S-LOC 10 Cats C/D ½ SM, and Circling and HOVUB INT minimums Circling Cats C/D ¼ SM. Circling Rwy 15, 28, 33 NA at night.

MISSED APPROACH: Climb to 1200 then climbing right turn to 2600 direct JOT VOR/DME and hold.

ATIS 132.075	CHICAGO APP CON 133.5 349.0	DUPAGE TOWER 120.9 257.8	GND CON 121.8	CLNC DEL 119.75
------------------------	---------------------------------------	------------------------------------	-------------------------	---------------------------



Remain within 10 NM				ELEV 759	TDZE 756	
3000 277° 097° 2501 2600 1300 3.6 NM 1.7 NM				1200 2600 JOT * LOC only. * 1340 when using Chicago/ Aurora altimeter setting.		
CATEGORY	A	B	C	D	097° TWR 895 MIRL Rwy 15-33 and 2R-20L TDZ/CL Rwy 2L RLS Rwy 10 REIL Rwy 10, 15, 28 and 33 HIRL Rwy 10-28 and 2L-20R FAF to MAP 5.3 NM Knots 60 90 120 150 180 Min:Sec 5:18 3:32 2:39 2:07 1:46	
S-ILS 10	956-¾ 200 (200-¾)					
S-LOC 10	1300-1	544 (600-1)	1300-1½	544 (600-1½)		
CIRCLING	1300-1 541 (600-1)	1360-1 601 (700-1)	1460-2 701 (800-2)	1460-2¼ 701 (800-2¼)		
HOVUB INT MINIMUMS (DUAL VOR RECEIVERS REQUIRED)						
S-LOC 10	1220-1	464 (500-1)	1220-1¾	464 (500-1¾)		
CIRCLING	1260-1 501 (600-1)	1360-1 601 (700-1)	1460-2 701 (800-2)	1460-2¼ 701 (800-2¼)		