

SPRING FIVE DEPARTURE

AL-5165 (FAA)

SPRINGDALE MUNI (ASG)
SPRINGDALE, ARKANSAS

GND CON
121.6
SPRINGDALE TOWER ★
118.2 (CTAF)
AWOS-3
124.675
RAZORBACK DEP CON ★
126.6 305.2
MEMPHIS CENTER
126.1 269.0
UNICOM
122.95

TOP ALTITUDE:
4000

BARTLESVILLE
117.9 BVO
Chan 126

SPRINGFIELD
116.9 SGF
Chan 116

DOGWOOD
109.4 DGD
Chan 31

RAZORBACK
116.4 RZC
Chan 111

TULSA
114.4 TUL
Chan 91

HARRISON
112.5 HRO
Chan 72

OKMULGEE
114.9 OKM
Chan 96

WILL ROGERS
114.1 IRW
Chan 88

FORT SMITH
110.4 FSM
Chan 41

LITTLE ROCK
113.9 LIT
Chan 86

HOT SPRINGS
110.0 HOT
Chan 37

TAKEOFF MINIMUMS

Rwy 18: Standard.
Rwy 36: 400-2½ or standard with minimum
climb of 332' per NM to 1900.

NOTE: RADAR required.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 18: Climb on heading 183° to 1900, then turn left heading 120°,
thence

TAKEOFF RUNWAY 36: Climb on heading 003°, thence

. . . . Expect radar vectors to filed/assigned route. Climb and maintain 4000.
Expect clearance to filed altitude/flight level ten minutes after departure.

LOST COMMUNICATIONS: If communications are not established within 2 minutes
after departure, climb and maintain 5000' and proceed direct RZC VORTAC, then
proceed on course.

SPRING FIVE DEPARTURE