


WAAS CH 70313 W35A	APP CRS 354°	Rwy Idg TDZE Apt Elev	7351 845 845
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35L

GRAND FORKS INTL (GFK)

RNP APCH. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.6°C or above 54°C. For Inop ALS, increase LNAV/VNAV Cat D visibility to RVR 5000 and LNAV Cat C/D visibility to RVR 5500.			MALS R	MISSED APPROACH: Climb to 2600 direct FODIB and hold.	
ATIS 119.4	GRAND FORKS APP CON ★ 118.1 318.1	GRAND FORKS TOWER ★ 118.4 (CTAF) 350.35	GND CON 124.575	CLNC DEL 135.725	UNICOM 122.95



VGSi and RNAV glidepath not coincident (VGSI Angle 2.76/TCH 61).				2600	FODIB
4 NM Holding Pattern				ERIXE	JAGBI
GP 3.00° TCH 55				6000 2600	354° 174°
				6 NM	4.3 NM 1 NM
CATEGORY	A	B	C	D	
LPV DA	1095/24 250 (300-½)				
LNAV/VNAV DA	1174/26 329 (400-½)				1174/40 329 (400-¾)
LNAV MDA	1200/24	355 (400-½)	1200/30 355 (400-¾)	1200/50 355 (400-1)	
CIRCLING	1280-1 435 (500-1)	1300-1 455 (500-1)	1400-1½ 555 (600-1½)	1400-2 555 (600-2)	

NC-1, 21 MAR 2024 to 18 APR 2024

NC-1, 21 MAR 2024 to 18 APR 2024