

VOR/DME FFM	APP CRS	Rwy Idg	5639
110.4	115°	TDZE	1182
Chan 41		Apt Elev	1183

VOR RWY 13

FERGUS FALLS MUNI/EINAR MICKELSON FLD (FFM)


▼

▲ NA

When local altimeter setting not received, use Elbow Lake altimeter setting and increase all MDAs 60 feet; increase Circling Cat C/D visibility ¼ SM. EBABY fix minimums increase S-13 Cat C/D and Circling Cat C/D visibility ¼ SM.

MISSED APPROACH: Climb to 3000 then left turn direct FFM VOR/DME and hold.

AWOS-3PT	MINNEAPOLIS CENTER	UNICOM
119.05	126.1 269.2	122.8 (CTAF) 0



VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 52).

Remain within 10 NM

2900

295°

115°

EBABY FFM 1.6

2.75°

TCH 50

*1640

3000

FFM VOR/DME

FFM

*1700 when using Elbow Lake altimeter setting.

1.6 NM

CATEGORY	A	B	C	D
S-13	1640-1	458 (500-1)	1640-1⅓	458 (500-1⅓)
CIRCLING	1640-1 457 (500-1)	1740-1 557 (600-1)	1820-1¾ 637 (700-1¾)	1940-2½ 757 (800-2½)
EBABY FIX MINIMUMS				
S-13	1580-1	398 (400-1)	1580-1⅓	398 (400-1⅓)
CIRCLING	1640-1 457 (500-1)	1740-1 557 (600-1)	1820-1¾ 637 (700-1¾)	1940-2½ 757 (800-2½)

