WAAS CH 93513 W01A	APP CRS 010°	Rwy ldg 6604 TDZE 87 Apt Elev 91

RNAV (GPS) RWY 1
H L SONNY CALLAHAN (CQF)

Baro-VNAV NA when using Mobile Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 43°C (109°F). DME/DME RNP-0.3 NA. VDP NA with Mobile Intl altimeter setting. When local altimeter setting not received, use Mobile Intl altimeter setting and increase LPV DA to 329 feet, LNAV/VNAV DA to 517 feet, and all MDA 60 feet; increase LNAV Cats C/D visibility ⅛ SM and Circling Cats C/D ¼ SM.

MISSED APPROACH: Climb to 700 then climbing left turn to 2000 direct BFM VORTAC and hold.

AWOS-3PT	MOBILE APP CON ★	UNICOM
118.425	118.5 269.3	123.0 (CTAF) L





CATEGORY	A	B	C	D
LPV DA	287-¾ 200 (200-¾)			
LNAV/VNAV DA	475-1⅜ 388 (400-1⅜)			
LNAV MDA	440-1 353 (400-1)			
CIRCLING	560-1 469 (500-1)	580-1 489 (500-1)	720-1¾ 629 (700-1¾)	740-2 649 (700-2)

SE-4, 21 MAR 2024 to 18 APR 2024