

WAAS

CH **65943**

W21A

APP CRS

215°

Rwy Idg

5000

TDZE

819

Apt Elev

819

RNAV (GPS) RWY 21

MADISON MUNI (IMS)

RNP APCH.

▼

▲

Circling NA for Cat C east of Rwy 03-21. Rwy 21 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.

MISSED APPROACH: Climb to 4000 direct KOYGE and hold, continue climb-in-hold to 4000.

AWOS-3


119.175

LOUISVILLE APP CON

132.075 327.0

UNICOM

123.0 (CTAF) 0



ELEV **819**

TDZE **819**

HIRL Rwy 3-21 0

REIL Rwy 21 0

215°

4000

KOYGE

4 NM

Holding Pattern

1.5

1.6 NM

2 NM

2 NM

3.8 NM

RW21

OHWOW

DORRE

FORAY

BEENO

1.5 NM to RW21

1900

230°

2400

2500

096°

276°

6000

2800

GP 3.20°

TCH 39

CATEGORY	A	B	C	D
LPV DA	1099- $\frac{7}{8}$	280 (300- $\frac{7}{8}$)		NA
LNAV/VNAV DA	1132- $\frac{7}{8}$	313 (400- $\frac{7}{8}$)		NA
LNAV MDA	1340-1	521 (600-1)	1340-1 $\frac{1}{2}$ 521 (600-1 $\frac{1}{2}$)	NA
CIRCLING	1340-1	521 (600-1)	1340-1 $\frac{1}{2}$ 521 (600-1 $\frac{1}{2}$)	NA