

WAAS
CH 97504
W36A

APP CRS
355°

Rwy Idg 6610
TDZE 164
Apt Elev 166

RNAV (GPS) RWY 36

HOUSTON EXEC (TME)

⚠

Baro-VNAV NA when using David Wayne Hooks Meml altimeter setting.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). DME/DME RNP-0.3 NA. VDP NA when using David Wayne Hooks Meml altimeter setting. When local altimeter setting not received, use David Wayne Hooks Meml altimeter setting and increase LPV DA to 471 feet, LNAV/VNAV DA to 719 feet; increase all MDA 60 feet. Increase LNAV/VNAV visibility ¼ mile all Cats and LNAV and circling Cat C/D ¼ mile.

MISSED APPROACH:
Climb to 2000 direct AGAXE and via 328° track to BIMTE and hold.

ATIS 119.525	HOUSTON APP CON 123.8 257.7	EXECUTIVE TOWER ★ 126.975 (CTAF) 0	GND CON 132.075	CLNC DEL 132.075	UNICOM 122.975
-----------------	--------------------------------	---------------------------------------	--------------------	---------------------	-------------------

MISSED APCH FIX

BIMTE

AGAXE

364

315

204

RW36

316

316

546

647

(FAF) ZATBA

2000

355°

(6)

(IAF) WAXUG

2000

085°

(5)

(IF) TIDUY

2000

265°

(5)

(IAF) CAROG

694

MSA RW 36 25 NM

3100

RADAR REQUIRED

ELEV 166

TDZE 164

81

6610 X 100

36

TWR

REIL Rwy 18-36

MIRL Rwy 18-36

355° to RW36

2000

AGAXE

328° tr

BIMTE

ZATBA

TIDUY

Procedure Turn NA

*INAV only.

1.3

4.3 NM

6 NM

1.3 NM to RW36

355°

2000

355°

GP 3.00° TCH 40

CATEGORY	A	B	C	D
LPV DA	414-1 250 (300-1)			
LNAV/VNAV DA	662-1¾ 498 (500-1¾)			
LNAV MDA	620-1	456 (500-1)	620-1¼ 456 (500-1¼)	620-1½ 456 (500-1½)
CIRCLING	820-1	654 (700-1)	860-2 694 (700-2)	1000-2¾ 834 (900-2¾)

HOUSTON, TEXAS

Amdt 1A 30DEC21

29°48'N-95°54'W

HOUSTON EXEC (TME)

RNAV (GPS) RWY 36