


LOC I-MCN	APP CRS	Rwy Idg
109.5	054°	6221
		TDZE
		344
		Apt Elev
		354

ILS or LOC RWY 5
MIDDLE GEORGIA RGNL (MCN)

DME and RADAR required.	MALSR	MISSED APPROACH: Climb to 800 then climbing right turn to 3000 on heading 090° and DBN VORTAC R-314 to TRUKR/DBN VORTAC 15 DME/RADAR and hold.
DME from MCN VORTAC. Simultaneous reception of I-MCN and MCN DME required. For inop ALS, increase S-ILS 5 Cat E visibility to RVR 4000 and S-LOC 5 Cats C, D, and E visibilities to 1 3⁄8 SM. * RVR 1800 authorized with use of FD or AP or HUD to DA.		

ATIS	ATLANTA APP CON *	MACON TOWER *	GND CON	UNICOM
120.775	124.2 279.6	128.2 (CTAF) 0 257.8	121.65	122.95



CATEGORY	A	B	C	D	E
S-ILS 5 *	544/24 200 (200-½)				
S-LOC 5	840/24	496 (500-½)	840/50 496 (500-1)		
C CIRCLING	900-1	546 (600-1)	920-1½ 566 (600-1½)	1120-2½ 766 (800-2½)	1180-3 826 (900-3)