# RNAV (GPS) RWY 13

TOPEKA RGNL (FOE)

| WAAS | APP CRS | Rwy Idg | 12803 |
|---|---|---|---|
| CH 66100 | 132° | TDZE | 1066 |
| W13A | | Apt Elev | 1078 |

RNP APCH.

When local altimeter setting not received, use Philip Billard Muni altimeter setting and increase all DA/MDA 60 feet, increase LPV all Cats visibility ⅛ SM, LNAV Cat C visibility ⅛ SM and Circling Cat D visibility ¼ SM. Baro-VNAV and VDP NA when using Philip Billard Muni altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C.

MALSF

MISSED APPROACH: Climb to 3000 direct ERJAG and hold.

| ATIS | KANSAS CITY CENTER | FORBES TOWER★ | GND CON | UNICOM |
|---|---|---|---|---|
| 128.25 | 123.8 343.7 | 120.8 (CTAF) L 340.2 | 118.425 275.8 | 122.95 |




ELEV 1078 D TDZE 1066




REIL Rwys 3, 13 and 21
MIRL Rwy 3-21 L
HIRL Rwy 13-31 L

ERJAG 132° 312° 5 NM




| CATEGORY | A | B | C | D |
|---|---|---|---|---|
| LPV DA | 1316-¾ 250 (300-¾) | | | |
| LNAV/VNAV DA | 1506-1½ 440 (500-1½) | | | |
| LNAV MDA | 1540-1 474 (500-1) | | 1540-1⅜ 474 (500-1⅜) | 1540-1½ 474 (500-1½) |
| C CIRCLING | 1540-1 462 (500-1) | 1580-1 502 (600-1) | 1580-1½ 502 (600-1½) | 1700-2 622 (700-2) |



NC-2, 18 APR 2024 to 16 MAY 2024
NC-2, 18 APR 2024 to 16 MAY 2024