WAAS	APP CRS	Rwy Idg	7020
CH 90215	038°	TDZE	3652
W03A		Apt Elev	3661

RNAV (GPS) RWY 3

LEA COUNTY RGNL (HOB)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C (-7°F) or above 52°C (126°F). DME/DME-RNP-0.3 NA. When local altimeter setting not received, use Carlsbad altimeter setting and increase all DA 281 feet and all MDA 300 feet, increase LPV and LNAV/VNAV all Cats visibility ½ mile, LNAV Cats C/D visibility ⅞ mile, Circling Cat C visibility ¾ mile, and Circling Cat D visibility ½ mile. Baro-VNAV and VDP NA when using Carlsbad altimeter setting. Inoperative table does not apply to LPV and LNAV/VNAV. For inoperative MALSR increase LNAV Cats C/D visibility to 1 mile. For inoperative MALSR when using Carlsbad altimeter setting, increase LPV and LNAV/VNAV all Cats visibility to 1¾ miles, and LNAV Cats C/D to 1⅞ miles. Rwy 17 helicopter visibility reduction below 1 SM NA. Circling Rwy 17 NA at night.

MALSR

MISSED APPROACH: Climb to 6000 direct DEKEC and hold.

ATIS	FORT WORTH CENTER	HOBBS TOWER ★	GND CON	UNICOM
119.75	133.1 298.95	120.65 (CTAF) 317.4	121.9	122.95



ELEV 3661 D TDZE 3652



MIRL Rwy 12-30 L
HIRL Rwy 3-21 L



CATEGORY	A	B	C	D
LPV DA	3902-¾ 250 (300-¾)			
LNAV/VNAV DA	3902-¾ 250 (300-¾)			
LNAV MDA	4020-½ 368 (400-½)		4020-⅝ 368 (400-⅝)	
C CIRCLING	4120-1 459 (500-1)	4160-1 499 (500-1)	4440-2¼ 779 (800-2¼)	4440-2½ 779 (800-2½)

SW-1, 18 APR 2024 to 16 MAY 2024
SW-1, 18 APR 2024 to 16 MAY 2024