

WAAS
CH **70434**
W33A

APP CRS
334°

Rwy Idg
TDZE
Apt Elev

4200
1379
1379

RNAV (GPS) RWY 33

EL DORADO/CAPT JACK THOMAS MEML (EQA)

▼

NA

RNP APCH-GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Colonel James Jabara altimeter setting and increase all DA 51 feet and all MDA 60 feet. Baro-VNAV and VDP NA when using Colonel James Jabara altimeter setting.

MISSED APPROACH: Climb to 3100 direct GOPHR and hold.

AWOS-3P
120.875

WICHITA APP CON
134.8 269.1

UNICOM
122.8 (CTAF)

MISSED APCH FIX

Procedure NA for arrivals at CAWBW on V73 northwest bound.

Procedure NA for arrivals at OBDRAW on V354 northbound and V350 eastbound.

MSA RW33 25 NM

ELEV **1379**

TDZE **1379**

HIRL Rwys 4-22 and 15-33

3100

GOPHR

* LNAV only.

WEXOS 1.7 NM to RW33

WAXFY 3000

BSHWD 4 NM Holding Pattern

1960*

3000

3100

GP 3.00° TCH 40

CATEGORY	A	B	C	D
LPV DA	1579-1	200 (200-1)	NA	
LNAV/VNAV DA	1629-1	250 (300-1)	NA	
LNAV MDA	1760-1	381 (400-1)	NA	
CIRCLING	1820-1 441 (500-1)	1960-1 581 (600-1)	NA	

EL DORADO, KANSAS

EL DORADO/CAPT JACK THOMAS MEML (EQA)

Amdt 1B 06OCT22

37°46'N-96°49'W

RNAV (GPS) RWY 33